



	ECG42COMBO2/1-I	ECG56COMBO3/1-I	ECG56COMBO2/2-I
No. of modules	12 + 2	12 + 2	24 + 4
PE, N terminal	2 x 10	2 x 10	2 x 13

	ECG70HCOMBO4/1-I	ECG70HCOMBO3/2-I	ECG70HCOMBO2/3-I
No. of modules	12 + 2	24 + 4	36 + 6
PE, N terminal	2 x 10	2 x 13	2 x 15

	A	B	C	H	W
ECG42COMBO2/1-I	592 mm	346 mm	92 mm	549 mm	306 mm
ECG56COMBO3/1-I	717 mm	346 mm	92 mm	673 mm	306 mm
ECG56COMBO2/2-I	717 mm	346 mm	92 mm	673 mm	306 mm
ECG70HCOMBO4/1-I	842 mm	346 mm	92 mm	799 mm	306 mm
ECG70HCOMBO3/2-I	842 mm	346 mm	92 mm	799 mm	306 mm
ECG70HCOMBO2/3-I	842 mm	346 mm	92 mm	799 mm	306 mm

For indoor locations (S 50% RH at max. +40°C
 or for example 90% RH at +20°C)
 Temperature range: -25°C ... +60 °C.
 Rating Voltage: AC400V; IP30, IK08
 According to: IEC 60670; IEC 62208

ETI Elektroelement d.o.o
Obrezija 5
1411 Izlake
Slovenia

ETI Polam Sp.z.o.o.
ul. Jana Pawła II 18
06-100 Pułtusk
Polska

TOOLS

